

## JP-312H

LED Array



## Specifications

Image Sensor  
TV System  
Image Resolution  
Horizontal Resolution  
Minimum illuminator  
S/N Ratio  
AES  
DNR  
OSD  
White Balance  
AGC  
BLC  
Gamma Adjusting  
synchronization System  
Video Output  
Voltage  
Operating Temperature  
Dimension (mm)  
Weight (g)

## FEATURES

- > 1/3" SONY CCD
- > 700 TVL, BLC/AWB Function
- > IR LED 3pcs, IR Range 100M
- > 3pcs 30U Array Led and 14pcs Led
- > Standard 9-22mm Lens Zoom Lens External lens adjusting
- > 3-Axis Cable Built-in Bracket Suitable for Wall Installation
- > OSD Menu Function
- > ATR Function
- > Water Resistant Rate:IP66

1/3" COLOR SONY Super HADII CCD  
PAL/NTSC  
PAL:976(H)x582(V), NTSC:976(H)x494(V)  
700TVL  
0.01LUX/F1.2, 0 LUX IR LED ON  
>58dB  
1/50-1/10,000sec (PAL)  
2D-DNR  
OSD  
ATW/Manual/Auto  
Auto/Manual  
BLC/HLC  
0.45  
Internal Synchronization  
1.0Vp-p,75 Ohm.  
DC12V, 700 mA  
-10°C ~ 50°C  
325(W) x 100(H) x 110(D)  
1258



>> We live in quality We win on service.

