



JP-HVD-360

IR Hevy-Duty Dome



FEATURES

- > 1/4" SONY Exview HAD CCD
- > Zoom 36X , Lens 3.4-122.4mm
- > Color 530 TVL. B/W 570 TVL
- > 0.7 Lux. B/W 0.01 lux
- > Night vision distance 80-100Meter
- > Support Multi Protocol,128 Preset,
- > Built-in Blower and Heater, IP66

Specifications

Power consumption
Signal System
Scanning system
Effective Pixel
Monitor method
Infrared light
Wiper
Night-vision distance
Rotation speed
Preset speed
Rotation
Preset
Auto-flip
Scan
Display zone
Alarm function
Sync Model
Video output
Remote controlling
Baud rate (RS485)
S/N Ratio
Electronic Shutter
Wide Dynamic Range
Privacy Masking Zone
Temperature
Humidity
Protection grade
Dimension (L*W*H)
Gross weight

45 W
PAL
2:1 Interlacing
752X582 HVX)
Manual/Time start-up setting
Manual/auto (As the intensity of ray to auto-open)
Manual
100m
Pan 0.4~90°/s, Tilt 0.4~60°/s
Pan160°/s, Tilt120°/s
Pan 360°continuously, tilt 180° (-90°~+90°), With auto-flip
128 preset, titles can be edited
Tilt down 90°, with auto-flip 180°
355°programmable, 4 scan
8 programmable zones with titles
7 alarm input / 2 alarm output
Internal/external
Female BNC
RS485/422 BUS, Manchester, BI-PHASE, Coaxial Video Control
2400 / 4800 / 9600 / 19200 bps
≥ 50dB
1/1 ~ 1/10,000s
Tes
24
Outdoor - 40 °C ~ + 60 °C
0~95% (Non-condensation)
IP66, 4500W lightning-proof, surge-proof, wave-proof, all-day defend cover
411*210*269 (H) mm.
9.5kg

>> We live in quality We win on service.

