

Features



JP-SP100

- JP-SP100 is suitable for protection video system
- Large current capacity
- Be connected with protection equipment
- Maintenance free
- Should check and sign work after thunder storm
- Convenient installation designd

Specifications

Anti-rush Time	1nS
Max Surge Current	4KA
Endurance	300 time attack (100Amps)
Coax Cable Standard Resistance	10000 Mohm
Surge Resistance	About 0 ohm
Bandwidth	0 ~ 1 GHz
Max Current Flow	130 VAC/DC 65Vrms at 10 Amps
Insertion Loss	Less than 0.2dB
Loop Resistance (75ohm)	16 dB
Max Flow of Power Supply	AC40V (Max) / DC 56V (Max)
Connector	Female BNC Terminals and Easy Fasten
Temperature	Operating -20 C to 75 C
Humidity	0 ~ 90 %
Weight	60 g
Dimension	73(L) x 25(W) x 25(H) mm

นำเข้า จัดจำหน่าย ติดตั้ง และบริการโดย



บริษัท ไออีเอส อินเตอร์คอนเน็ค (ประเทศไทย) จำกัด
IES Interconnect (Thailand) Co.,Ltd

338/288-289 Soi Ladprao 87 (Jantrasuk) Ladprao Rd. Wangthonglang Bangkok 10310

Tel : 0-2935-9900 Auto Fax : 0-2935-9950 www.wann.co.th